

NX623T RADIOSCOPIC INSPECTION SYSTEM



National X-Ray Corp. continuously researches and integrates the latest technology in X-ray image detection systems to produce high performance inspection systems that match the specific needs of the customer application. Easily integrated into the Non-Destructive lab, or implemented directly on the production floor, this ergonomic, simple to operate and highly capable X-ray System yields immediate results. Along with the various automation modules, image processor and equipped with other optional control software packages, this fully configurable NN623T Radioscopic Inspection System fulfills the requirements of today's SPC/Inspection demands. Digital panels, Digital Camera and Image Intensifier Systems, along with a wide variety of x-ray systems and manipulator sub-systems, make this system the ideal Non-Destructive Testing system.

Features

- ◆ Basic system includes advanced analog or digital image intensifier systems coupled to high resolution, no-burn camera modules
- ◆ Ultra-compact overall design minimizes floor-space requirements
- ◆ X-Ray energies ranging from 80kV to 225kV depending on application needs
- ◆ Wide dynamic operating range
- ◆ Large bi-parting loading door for fast, simple test part loading
- ◆ Heavy Duty Six-axis test part manipulator eliminates most test part repositioning
- ◆ Basic system requires only standard electrical supply
- ◆ Wide range of optional sub-systems available that include Gulmay & Comet
- ◆ Advanced Image Processing "NXi-RAD"
- ◆ Image archiving, LAN ready, internet mail compatible, printing ready
- ◆ Digital imaging (film-less) in various formats (a-Si Panels, CMOS detectors, Linear Detectors)
- ◆ American Designed, Build and parts readily available from local vendors

NX623T System Specifications

Application Range

- Penetration of up to 6" of Al, or 1.5" Fe
- Test Sample weights up to 150 lbs
- Sample sizes up to 24" x 36" (Cyl. Volume)
- ASTM E-155, MIL standards & others

Inspection Enclosure

The NX623T x-ray system is manufactured in compliance with all federal, state and local radiation safety regulations (CFR 1020.40). A sliding bi-parting loading door is provided for ease of use and is fully safety interlocked. When opened, the doors action disables x-ray production. The bi-parting loading door contains a lead-glass (Pb) window to allow the operator to view the interior of the enclosure during inspection routines.

Dimensional Data (approximate):

- Enclosure only: 87" W x 75" Deep x 78" H
- Loading Door Opening: 30"W x 46"H
- Lead-Glass Viewing Window: 10" W x 12" H
- Control Console:
 - Single bay: 24" W x 27" D x 74" H
 - Double Bay: 46" W x 27" D x 74" H
 - Writing Surface: Add 19" depth
- Approximate Weight of entire system: 7500 lbs

Manipulator

6-Axis type including:

- X-Axis: +/- 12" (24" Ttl) •Y-Axis: 36"
- Z-Axis: 24" •Tilt Axis: +/- 30 degrees
- Rotation: 360° CW/CCW (12" diameter Table)
- Capacity: 150 lbs

Control Console

The control console contains all necessary components for system control:

- Microprocessor-based X-ray Controller
- Operator Interface for Imaging and Manipulation
- Writing Surface
- Single or Dual bay
- System Control Electronics

Utilities


- 230 VAC ±10%, 60 Hz, 40A, 4-Wire (L1, L2, Neutral, Ground)

X-ray System

- 160kV or 225kV conventional or micro-focus - depending on App. System Shown: Gulmay FC160, MP-1 Controller

National X-Ray Corp. reserves the right to change products specifications without prior notice, as part of an ongoing production improvement program.

National X-Ray Corp.
4181 Tanners Creek Drive
Flowery Branch, GA 30542
PH: 678.960-0080
FAX: 678.960-0080
E-mail: info@nationalx-ray.com
Web: www.nationalx-ray.com



Imaging System

The imaging system is matched to your particular application requirements and could include:

- Digital or Analog Image Intensifiers
- Digital Panel Technology (a-Si, CMOS, etc.)
- Direct View Digital Systems
- Linear Detector Technology

Options

- Image Processing and/or System Control Module
- Full SPC Database Capability
- Image Archiving
- PC Network Capability
- X/Y Image Intensifier X/Y Shutters
- Tubehead Shutter
- Laser Alignment
- Interior Viewing CCTV Camera
- CT Capability



Shown is the C-Arm based manipulator as seen from the opened loading



The loading table shown extended out from the loading door for ease of loading heavy parts

Distributor:

National X-Ray Corp. Products & Services

STANDARD CABINET SYSTEMS

CUSTOM SYSTEMS DIGITAL

X-RAY IMAGE DETECTORS

CONSTANT POTENTIAL X-RAY SYSTEMS

STANDARD CABINET SYSTEMS

MICRO-FOCUS X-RAY SOURCES

WELD INSPECTION SYSTEMS

IMAGE PROCESSING & SYSTEM CONTROL ADR SOLUTIONS

COMPUTED FILMLESS RADIOGRAPHY SYSTEMS

COMPLETE NATIONWIDE FIELD & FACTORY LEVEL SERVICE